

Philbrick Associates

P.O. Box 188, Hillcrest 3650
Tel/Fax: +27 (0)31 7763917
Cell: +27 (0)82 9015597
Email: philas@3i.co.za

TECHNICAL DATA SHEET

DURA-FLEX TOPCOVER

2 Pack Bitumen Emulsion with Hifilled Binder System

DESCRIPTION

A high filled bitumen emulsion/flexible polymer system utilised to provide superior binding, wearing and aesthetically pleasing surfaces to asphalt and/or compacted gravel surfaces such as dirt roads, bund walls, parking areas and walkways.

PRODUCT TYPE

2 pack selected bitumen emulsion/flexible polymer liquid concentrate with carbon enriched dry filler.

USES

Dirt Roads
Bund Walls
Parking Areas
Walkways

ADVANTAGES

Superior binding of friable surfaces and subsequent high wear resistance.

MIXING

Add 5 litres of water to the 20kg bag of Filler in a suitable container.
Then add the 5 litres of Liquid Concentrate and mix to a smooth paste.
Additional water not exceeding 5 litres can be added to obtain the required consistency.

SURFACE PREPARATION

Ensure that the substrate is free of oil, grease or fungal growth.

APPLICATION

Apply one coat by brush or squeegee to between a minimum of 1mm to a maximum of 6mm as required.

CLEANING TOOLS AND APPLICATION EQUIPMENT

Whilst still wet clean with water.
Should the Topcover has been allowed to dry, clean with a suitable solvent based brush cleaner.

PROPERTIES

Density	1,8g/cm ³
Colour	Black
Finish	Sheen
Flash Point	None (waterbased)
Dilution	Water
Volume Solids	60%
Consistency	Thixotropic Liquid
Coverage	15 m ² per unit pack
Shelf Life	12 months from date of manufacture in sealed containers
Storage Conditions	Store undercover in a cool conditions. Protect from frost.
Packaging:	
1. Liquid Component	5 litre Plastic Bucket
2. Filler	20 KG Bag

COMPILED BY:

DICK PHILBRICK F.T.S.C.
P.O.BOX 188, HILLCREST, 3650
KZN, RSA

Philbrick Associates

P.O. Box 188, Hillcrest 3650
Tel/Fax: +27 (0)31 7763917
Cell: +27 (0)82 9015597
Email: philas@3i.co.za